



XK3118T1+ / XK3118T1-D+

2018 12



00000577



知 何



3.6

" "

			" " (Funtion)
1	" " " " " ←"	Fn **	ANL Cot LoC AN2 AN3 --
2	" " " " " ←"	PS **	(Power Save) oFF oN onP
3	" " " " " ←"	br****	(Baud rate) 600 9600bps
4	" " " " " ←"	Co *	(Communicate Mode) 1 6
5		H*****	(High): " " " " " ←" 2000
6		L*****	(Low): " " " " " ←" " HI" " LO" " OK" 1000
7		r*****	
8		t **	

1 " " ON r t

2 oFF r " "

L " " t

" " " " " " 30" "

" " " " " ←"



1 8 23.45kg ASCII =54.3200





1		XK3118T1+/XK3118T1-D+	1	
2		XK3118T1	1	
3		D 9 ()	1	
4	D	DB-9	1	
5		HKCT-10(M12× 0.75)(5)	1	
6		XK3118T1 ()	1	
7	1	M4× 12	4	
8	2	M6× 25	1	
9	1	M4	4	
10	2	M6	1	
11		110~220VAC 10.5VDC	1	XK3118T1+



1		A5	A4
2		70g	200g
3			
4			
5		70g	80g
6			
7			

柯力